

# TWN3 MULTI125

## 125kHz Contactless Reader/Writer





The TWN3 Multi125 transponder reader is designed for easy integration into various applications.

The device supports either USB or RS232 communication just in dependence on the connection cable and is available as ready-to-connect desktop reader in a slim line black or white housing or as a OEM board (PCB) without housing for direct integration into embedded applications.

Readers can be programmed with a script language for autonomous execution of even complex commands like login procedures, increment/decrement functions and many more.

Technical Data	
Housing	Material ABS UL94-V0, colour black or white
Frequency	125 kHz
Dimensions	Desktop Reader: 88mm x 56mm x 18mm / 3.5inch x 2.2inch x 0.7inch OEM Board: 76mm x 49mm x 14mm / 3.0inch x 1.9inch x 0.6inch
Power Supply	5V ± 10% via communication cable (USB); serial version requires external power supply
Supply Current	130mA typ. (USB, normal operation); 220mA peak
Temperature Range	Storage: -45°C up to +85°C (-49°F up to 185°F) Operating: -25°C up to +80°C (-13°F up to 176°F)
Antenna	Aircoil
R/W Distance	up to 100 mm / 4 inch (depending on transponder)
Host Interfaces	USB, RS232.
OS Support	Windows XP, Vista, 7(32/64 bit), 8, 8.1 and Linux
Communication Parameters	USB: Full speed (12 MBit) RS232: Baudrate: 9600 Parity: none, even, odd
Modes of Operation	USB keyboard emulation USB virtual COM port (bi-directional communication) Direct access to built-in RFID module (transparent mode)
Special Features	Powerful scripting language
Supported Transponders	<ul style="list-style-type: none"> <li>▪ EM4100, EM4102, EM4105, EM4200<sup>2)</sup></li> <li>▪ EM4050, EM4150, EM4450, EM4550</li> <li>▪ FDX-B</li> <li>▪ HITAG 1<sup>3)</sup>, HITAG 2<sup>3)</sup>, HITAG S<sup>3)</sup></li> <li>▪ Miro</li> <li>▪ Q5<sup>1)</sup></li> <li>▪ T5557<sup>1)</sup>, T5567<sup>1)</sup>, T5577<sup>1)</sup></li> <li>▪ TITAN (4050), UNIQUE, ZODIAC</li> </ul>
Certifications	CE, Australia, EAC, FCC, IC, RoHS-II compliant
Weight	Approximately 15g (without housing)
Order Code	OEM board Desktop reader: T3DO-N USB black: T3DT-NB2BEL USB white: T3DT-NB2WEL Serial black: T3DT-NR2BEL Serial white: T3DT-NR2WEL

<sup>1)</sup> Only Manchester f/64, sequence terminator off <sup>2)</sup> Only emulation of 4100,4102 <sup>3)</sup> Without crypto

Accessories					
Order Code	Snap-in holder HKSI-B - black, HKSI-W - white		Bracket Holder HKBR-B -black, HKBR-W - white		CAB-B2 - USB cable 200cm / 78.74inch CAB-B4 - USB cable 45cm / 17.72inch CAB-B7 - USB cable 120cm / 47.24inch
Order Code	PWA-EU - Power Supply (EU) PWA-AUS - Power Supply (AU)		PWA-US - Power Supply (US) PWA-UK - Power Supply (UK)		CAB-M1 - USB cable mini 12cm / 4.72inch CAB-R2 - RS232 cable 200cm / 78.74inch

## Drawing/Pin Out

Refer to document DS\_TWN3 Pinout & Cables

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names are registered trademarks. © 2015 Elatec GmbH – DocRev6 – 08/2015