



**SOKEYMOT**

**DISC STICKER TAG  
Q5**

Description	Disc Sticker tag designed to suit most LF applications		
<b>IC type:</b>	Q5 (5555)		
<b>Physical:</b>	Diameter:	25.00 mm	± 0.50 mm
	Thickness:	1.00 mm	± 0.05 mm
	Color:	White	
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Storage temp:</b>	-10°C to +50 °C	(+14°F to +122 °F)	ISO/IEC 10373
<b>Operating temp:</b>	-10°C to +50 °C	(+14 °F to +122 °F)	ISO/IEC 10373
<b>Mechanical:</b>	Vibration	IEC 68-2-6	
	Shock	IEC 68-2-29	
	Drop test 10 times 10 cycles (1.8m)		
<b>Material:</b>	PVC with 3M adhesive on one side		
<b>Printing:</b>	One side is printable with various technologies		
<b>Options:</b>	For full options list, please visit our website: <a href="http://www.aaitg.com">www.aaitg.com</a>		
<b>Part number:</b>	612510		

© ASSA ABLOY ITG reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. ASSA ABLOY ITG declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.2.202 – V1 - DefKey: 3314315 - 12.09.2007 - Page: 1 of 1

ASSA ABLOY Identification Technologies GmbH, Am Klängenweg 6A, 65396 Walluf, Germany Tel: +49 6123 791 0 Fax: -110 email: [info@aaitg.com](mailto:info@aaitg.com) web: [www.aaitg.com](http://www.aaitg.com)