



uTrust 3700 F

Contactless Smart Card Reader

CONVENIENT

Modern, compact casing design for easy and ergonomic operation in limited-space environments

CONVERGENT

Features contactless and NFC technologies for use with mixed credential populations and form factors

INTEROPERABLE

Supports major card ICs, standards and technologies in just one device

■ FAST

Transaction time optimized with 848 kbs support in ISO/IEC 14443 for maximum end-user acceptance

READY TO USE

Driver support for all major PC operating systems

Identiv's uTrust 3700 F is the ideal combination of contactless and near field communication (NFC) technologies in just one single device. Featuring 13.56 MHz contactless technology and NFC, this PC-linked reader supports end-user environments where virtually all kinds of contactless credentials are being used, even in mixed populations.

With its all-in-one concept, the uTrust 3700 F enables a smooth transition from well-established traditional technologies into emerging NFC applications, supporting new business. It represents the perfect mix between modern, stylish design and the same ergonomic operation of any credential form factor, like ID-1 cards, tokens or NFC-enabled smart phones. The Identiv driver platform, as well as the Windows® Plug-and-Play driver support, allow seamless integration into any end-user environment with very little or no administration. The uTrust 3700 F can even be used on Android- based systems.

With uTrust 3700 F, the end user experiences convenience, transaction-time efficiency, security, flexibility and full NFC capability for applications such as network log-on, secure web-based transactions and even NFC-based customer loyalty programs. The product also has been designed for secure in-field firmware upgrades and great reliability, providing a perfect return on investment.

Optional Accessory

uTrust 3700 F can be ordered with a pre-assembled standing base kit:

- Convenient End-user friendly reader presentation
- Flexibile Best reader positioning and orientation for mounting and ease of use
- Fitting-Ready Desktop mounting option

Advisory note: Identiv is rebranding the SCR and CLOUD products under the uTrust brand name. If you have further questions, please use the contact details on the following page.



Lascom cards
Calypso, CD21, NFC Forum Tag types 1/2/3/4 Data Transfer Rate
Antenna Integrated Driver and Software PC/SC specification ver. 2.01.14 for:
Driver and Software PC/SC specification ver. 2.01.14 for:
PC/SC specification ver. 2.01.14 for: • Windows® 7/8/ 8.1/10 (32 and 64 Bit) • Windows® Server 2003/2008/2012 • MacOS 10.10.x,10.11.x, 10.12.x • Linux 2.6.x (32 and 64 bit) • Android 4.0 and higher Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
• Windows® 7/8/ 8.1/10 (32 and 64 Bit) • Windows® Server 2003/2008/2012 • MacOS 10.10.x,10.11.x, 10.12.x • Linux 2.6.x (32 and 64 bit) • Android 4.0 and higher Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
PC/SC Driver • Windows® Server 2003/2008/2012 • MacOS 10.10.x,10.11.x, 10.12.x • Linux 2.6.x (32 and 64 bit) • Android 4.0 and higher Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
 MacOS 10.10.x,10.11.x, 10.12.x Linux 2.6.x (32 and 64 bit) Android 4.0 and higher Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
• Android 4.0 and higher Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
Software PC/SC API Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
Operating Conditions Power Supply Bus-powered USB Power Consumption 50mA , excluding card Dimensions $91 \times 75 \times 12 \text{ mm}$ ($3.583 \times 2.953 \times 0.472 \text{ in}$) $94 \times 77 \times 69 \text{ mm}$ ($3.386 \times 3.031 \times 2.717 \text{ in}$) Weight $44 \text{ g} \pm 5\%$ ($0.097 \text{ lb} \pm 5\%$) $84 \text{ g} \pm 5\%$ / $104 \text{ g} \pm 5\%$
Power Supply Bus-powered USB Power Consumption 50mA, excluding card Dimensions $91 \times 75 \times 12 \text{ mm}$ (3.583 × 2.953 × 0.472 in) $94 \times 77 \times 69 \text{ mm}$ (3.386 × 3.031 × 2.717 in) Weight $44 \text{ g} \pm 5\%$ (0.097 lb $\pm 5\%$) $84 \text{ g} \pm 5\%$ / $104 \text{ g} \pm 5\%$
Power Consumption 50mA, excluding card Dimensions 91 x 75 x 12 mm (3.583 x 2.953 x 0.472 in) 94 x 77 x 69 mm (3.386 x 3.031 x 2.717 in) Weight 44 g ± 5% (0.097 lb ± 5%) 84 g ± 5% / 104 g ± 5%
Dimensions $91 \times 75 \times 12 \text{ mm} (3.583 \times 2.953 \times 0.472 \text{ in})$ $94 \times 77 \times 69 \text{ mm} (3.386 \times 3.031 \times 2.717 \text{ in})$ Weight $44 \text{ g} \pm 5\% (0.097 \text{ lb} \pm 5\%)$ $84 \text{ g} \pm 5\% / 104 \text{ g} \pm 5\%$
Weight $44 \text{ g} \pm 5\% (0.097 \text{ lb} \pm 5\%)$ $84 \text{ g} \pm 5\% / 104 \text{ g} \pm 5\%$
Operating Temperature Pange 0° to E0°C (22° to 122°E)
Operating Temperature Range 0° to 50°C (32° to 122°F)
Storage Temperature Range -25 to 85°C (-4 to 140°F)
Operating Humidity Range Up to 95% RH non-condensing
MTBF ~10M hours
Connector 1.5 m USB cable with USB type A connector
Status Indicator LED
Firmware SmartOS TM
Firmware In-Field Upgradeable Yes
Certifications/Compliances
Systems/Standards USB 2.0 Full Speed, CCID, Microsoft® WHQL
Regulatory/Environmental CE, FCC, UL94, UL60950, VCCI, RFLJ, RoHS2, REACH, WEEE
Ordering Information
Product Part Number 905503; 905502-1 905503_5001

Identiv (NASDQ: INVE) is the leading global player in physical security and secure identification. Identiv's products, software, systems, and services address the markets for physical and logical access control and a wide range of RFID-enabled applications. Customers in the government, enterprise, consumer, education, healthcare, and transportation sectors rely on Identiv's access and identification solutions. Identiv's mission is to secure the connected physical world: from perimeter to desktop access, and from the world of physical things to the Internet of Everything. Identiv has offices worldwide. Addresses and phone numbers are listed at identiv.com/contact. For more information, visit identiv.com or email sales@identiv.com.

Technical data is subject to change without notice.